

ART.	CODE CÓDIGO
784 XL	8.48.50.23

TECHNICAL FEATURES

- Innovative blade tensioning device with clutch to check and adjust the proper tensioning of the blade (patented)
- Powerful 1200 W universal motor
- Digital electronic speed regulator "Constant Speed" with amperometric limiting device
- Die-cast vice with prismatic guides
- Easy to carry: only 17 Kgs

STANDARD EQUIPMENT

- Adjustable bar stop-rod for mass-produced cuts
- Tool for changing blade
- Filter-circuit for electromagnetic interference damping according to rules in force







CARACTERÍSTICAS TÉCNICAS

- Innovador tensor mediante embrague para el control y la regulación del correcto tensado de la hoja (patentado)
- Potente motor universal 1200 W
- Regulación electrónica de velocidad "velocidad constante", con limitador amperimétrico y protección térmica
- Mordaza moldeada a presión con guías prismáticas
- Sólo 17 kg de peso para la máxima portabilidad

EQUIPAMIENTO DE SERIE

- Varilla tope regulable para realizar cortes en serie
- Herramienta para el cambio de la hoja
- Circuito-filtro para la eliminación de interferencias electromagnéticas conforme con las normativas vigentes



	CUTTING CAPACITY	CAPACIDAD DE CORTE	
0°			
0°	120x115 mm	120 mm	119x119 mm
45°			
45°	85x70 mm	85 mm	80x80 mm



- Cutting capacity up to \varnothing 120 mm and up to \square 120 x 115 mm
- Capacidad de corte hasta \varnothing 120 mm y hasta \square 120 x 115 mm




- Powerful motor with digital electronic speed regulator
- Potente motor con regulación electrónica de velocidad



1200 \square




1440x13x0,65



8/12*



30 + 80



900x400x520



17

*Standard bimetal cobalt blade | De serie hoja bimetálica al cobalto
 \square 230 Volt - Hz 50 single-phase motor - Motor monofásico 230 Volt - Hz 50